























Power Rating	3.8kW, 240V, 50Hz
Min. Water Pressure	0.2bar / 20kPa / 2.9psi
Min. Water Flow Rate	1.6l/min
Inlet / Outlet Water Connector	Ø15mm
Temperature Control	Stepless Electronic
Product Dimension WxDxH	236 x 87 x 259 (mm)
Water Heater Nett Weight	1.2kg

3+2 **SPRAY PATTERNS** SHOWER

*Additional two combination spray patterns (1+3) and (2+3)



SCRATCH

RESISTANCE

EXTRA SAFETY DPDT PROTECTION SYSTEM

Double Thermal safety cut-off, ensure automatic halt to the temperature if it exceeds a certain point.

- 55°C Anti-scalding auto cut-off (Auto Reset)
- 80°C Abnormal overheat cut-off (Manual reset is required)



SPLASH PROOF CASE COVER WITH **IEC INSULTED PROTECTION**

Comply with IEC approved Splash Proof Protection (IP25 STandard) water-proof cover to avoid any water seepage into the heater.



1. MASSAGE







3. WIDE



The matte finishing on the CUBO water heater ensures that scratches will be reduced to a minimal.



UL-APPROVED HIGH QUALITY UK TECHNOLOGY HEATING ELEMENT

Ensuring peace of mind with quality and reliable UL-approved heating element.





RCP WM RM251 / EM RM264

















rubine.com.my

FIAMMA TRADING SDN. BHD. (330476-P) A Member of Fiamma Holding Berhad 2-1, Wisma Fiamma, No. 20, Jalan 7A/62A,Bandar Manjalara, 52200 Kuala Lumpur.





